

TABULAR-DESCRIPTION

ILS Z RWY 09R CAT II & III (VOBL)											
Serial-Number	Path-Descriptor	Rec Navaid	Waypoint-Identifier	Fly-Over	Course-°M(°T)	Distance-(Nm)	Turn-direction	Altitude-(ft)	Speed-limit-(Kts)-	VPA/-TCH-°ft	Navigation-Specification
010	IF	-	BL206	-	-	-	-	-FL090 +6000	-185	-	RNAV 1
020	TF	-	BL205	-	242.28(240.45)	5.16	-	-	-	-	RNAV 1
030	TF	-	BL204	-	182.26(180.43)	3.09	-	-	-	-	RNAV 1
040	TF	-	BL201	-	122.26(120.43)	3.10	-	@6000	-	-	RNAV 1
010	IF	-	BL453	-	-	-	-	-FL080 +6000	-185	-	RNAV 1
020	TF	-	BL205	-	143.18(141.35)	3.32	-	-	-	-	RNAV 1
030	TF	-	BL204	-	182.26(180.43)	3.09	-	-	-	-	RNAV 1
040	TF	-	BL201	-	122.26(120.43)	3.10	-	@6000	-	-	RNAV 1
010	IF	-	BL459	-	-	-	-	-FL090 +7000	-185	-	RNAV 1
020	TF	-	BL203	-	347.48(345.65)	3.68	-	-	-	-	RNAV 1
030	TF	-	BL202	-	062.25(60.42)	3.01	-	-	-	-	RNAV 1
040	TF	-	BL201	-	092.26(90.43)	3.02	-	@6000	-	-	RNAV 1
010	IF	-	BL201	-	-	-	-	@6000	-	-	-
020	CF	IBLN	FAP	Y	092.33(90.50)	2.50	-	@6000	-	-	-
030	CF	IBLN	RW09R	Y	092.33(90.50)	9.34	-	@3024	-	-3.00 / 51.4	-
040	DF	-	BL207	-	092.33(90.50)	-	-	+FL090	-185	-	RNAV 1
050	HM	-	BL207	Y	092.00(90.17)	1 MIN	L	+FL090	-210	-	RNAV 1
010	HM	-	BL453	Y	182.00(180.17)	1 MIN	L	+7000	-210	-	RNAV 1