

TABULAR DESCRIPTION RNAV 1 SIDs RWY 28 VIND:-

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	Distance/ Time NM/Min	VA °	Navigation Specification
BISUR 1B (CONDITIONAL)										
10	VA			280.98° Mag / 281.73° True		+1700	-250.00	-		RNAV 1
20	DF	DP791			R	-5000	-250.00			RNAV 1
30	TF	ND420		15.83° Mag / 16.58° True		-FL060		15.10		RNAV 1
40	TF	BISUR		71.91° Mag / 72.66° True				58.62		RNAV 1
IBANI 1B (CONDITIONAL)										
10	VA			280.98° Mag / 281.73° True		+1700	-250.00			RNAV 1
20	DF	ND080			L	-5000	-250.00			RNAV 1
30	TF	SKA		230.41° Mag / 231.16° True		-FL070		26.56		RNAV 1
40	TF	ND405		181.85° Mag / 182.60° True		-FL120		26.37		RNAV 1
50	TF	ND402		187.82° Mag / 188.57° True				20.19		RNAV 1
60	TF	ND403		193.21° Mag / 193.96° True				74.81		RNAV 1
70	TF	IBANI		171.79° Mag / 172.54° True				51.84		RNAV 1
ITBAN 1B										
10	VA			280.98° Mag / 281.73° True		+1700	-250.00			RNAV 1
20	DF	DP672			L	-4000	-250.00			RNAV 1
30	TF	ITBAN		136.02° Mag / 136.77° True				11.91		RNAV 1
LKN 1B										
10	VA			280.98° Mag / 281.73° True		+1700	-250.00			RNAV 1
20	DF	DP672			L	-4000	-250.00			RNAV 1
30	TF	ALI		103.83° Mag / 104.58° True				33.99		RNAV 1
40	TF	ND151		110.19° Mag / 110.94° True				76.18		RNAV 1
50	TF	LKN		115.12° Mag / 115.87° True				82.62		RNAV 1
LOVGA 1B										
10	VA			280.98° Mag / 281.73° True		+1700	-250.00			RNAV 1
20	DF	ND080			L	-5000	-250.00			RNAV 1
30	TF	SKA		230.41° Mag / 231.16° True		-FL070		26.56		RNAV 1
40	TF	ND405		181.85° Mag / 182.60° True		-FL120		26.37		RNAV 1
50	TF	LOVGA		212.68° Mag / 213.43° True				27.32		RNAV 1
LUN 1B										